



Part Number: 9985

Hook-Up/ Lead Wire, UL AWM Style 1061, (1) 26 AWG (7x34) TC, PVC, 300V RMS, 80°C

Request Sample
Requ

Product Description

One 26 AWG stranded (7x34) tinned copper conductor, PVC insulation.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Mater	ial	No. of Conductors
26	7x34	TC - Tinned	Copper	1
Conductor Count: 1		1		
Condu	Conductor Size:		26 AWG	3

Insulation

Ma	terial	Nominal Diameter	Nominal Wall Thickness
PVC - Poly	vinyl Chloride	0.039 in	0.01 in

Outer Jacket Material



Electrical Characteristics

Shielding: Unshielded

High Frequency (Nominal/Typical)

Nom. Insertion Loss 6.6 dB/100m

Unbalanced Crosstalk

Typical Unbalanced FEXT % 6.6 MHz

Voltage

Non-UL Voltage Rating	UL Voltage Rating
300 V	300 V

Temperature Range

Non-UL Temp Rating:	80°C
UL Temp Rating:	80°C

Mechanical Characteristics

			i e
Bulk Cable Weight:	1.5 lbs/1000ft		

Standards

UL Rating:	300V RMS, 80°C
UL AWM Style:	AWM 1061
CSA Rating:	300V RMS, 80°C
CSA AWM Specification:	AWM I A/B

CSA Type:	AWM I, A/B
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Part Number

Variants

Item #	Color	Footnote
9985 010100	Black	
9985 0101000	Black	Р
9985 013100	Blue, Dark	
9985 0131000	Blue, Dark	Р
9985 001100	Brown	
9985 0011000	Brown	Р
9985 008100	Gray	
9985 0081000	Gray	Р
9985 005100	Green, Dark	
9985 0051000	Green, Dark	Р
9985 003100	Orange	
9985 0031000	Orange	Р
9985 002100	Red	
9985 0021000	Red	Р
9985 009100	White	
9985 0091000	White	Р
9985 004100	Yellow	
9985 0041000	Yellow	Р

Footnote: P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.