

Tripp Lite

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

700W PowerVerter Ultra-Compact Inverter with 3 Outlets

MODEL NUMBER: PV700HF



Description

Utilize your vehicle's battery to efficiently power appliances, small electronics and office equipment on the road. Continuously supplies up to 700W of 120V AC power to 3 AC outlets from any 12V battery. Featuring an ultra-compact, lightweight design with metal housing, the PV700HF is the most rugged inverter available.

NOTE: To protect against high current draw that may occur during inverter failure, a fuse link rated at 125a should be positioned no more than 18" from the PV700HF's battery in the positive line.

Features

- Provides 120V AC power for a variety of mobile applications
- 700W continuous output power; 1400W peak output power (instantaneous)
- 3 AC outlets
- Ultra-compact extruded aluminum housing stands up to the toughest environments
- Cooling fan lengthens inverter service life & maintains cool operation
- Integrated mounting feet assure safe fixed installation
- Low battery alarm/shutdown detects low battery voltage and shuts down inverter
- Overload alarm/shutdown detects wattage overload on inverter outlets and shuts down inverter as a
 protective measure
- DC input terminals provide a solid connection to battery with user-supplied cables
- Lighted on/off switch shows inverter operations in cramped or dark environments
- Grooved surface for more efficient cooling

Specifications

Highlights

- 700W continuous output;
 1400W peak output
 (instantaneous)
- Converts 12V DC (battery)
 power into 110-120V AC
 (household) power; 3 AC outlets
- Installs in minutes (integrated mounting feet included)
- Provides a quiet alternative to generator noise and fumes
- Includes "battery saver" low voltage alarm/shutdown

Package Includes

- PV700HF Ultra-Compact DC-to-AC Inverter
- Instruction manual with warranty information



| OVERVIEW | |
|--|--|
| UPC Code | 037332137999 |
| ОИТРИТ | |
| Nominal Output Voltage(s) Supported | 120V |
| Frequency Compatibility | 60 Hz |
| Output Receptacles | (3) 5-15R |
| Output (Watts) | 700 |
| Continuous Output Capacity (Watts) | 700 |
| Peak Output Capacity (Watts) | 1400 |
| Output Voltage Regulation | Maintains PWM sine wave output voltage of 115 V AC (+/- 8 V AC) |
| Output Frequency Regulation | 60 Hz (+/- 3 Hz) |
| INPUT | |
| Recommended Electrical Service | Requires 12V DC input source capable of delivering 80A for the required duration (when used at full capacity). For automotive applications, hardwire installation with 125A battery system fusing is recommended |
| Maximum Input Amps / Watts | Full continuous load - 80A at 12V DC, No load - 0.95A at 12V DC, Shutdown - 150 micro amps |
| Input Connection Type | Set of 2 DC bolt-down wiring terminals |
| Input Cord Length Details | User supplies cabling. Minimum gauges for full load operation: 6 gauge or larger (see instruction manual) |
| Voltage Compatibility (VDC) | 12 |
| BATTERY | |
| DC System Voltage (VDC) | 12 |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | Lighted on/off power switch |
| Audible Alarm | Dual-function alarm indicates overload conditions or low DC input voltage of 10.5V or less |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 3.700 x 10.100 x 6.300 |
| Shipping Dimensions (hwd / cm) | 9.40 x 25.65 x 16.00 |
| Shipping Weight (lbs.) | 3.5000 |
| Shipping Weight (kg) | 1.59 |
| Unit Dimensions (hwd / in.) | 2.75 x 8.17 x 5 |
| Unit Dimensions (hwd / cm) | 7 x 20.75 x 12.6 |
| Unit Weight (lbs.) | 2.8 |
| Unit Weight (kg) | 1.27 |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

| Cooling Method | Fan |
|-------------------------------------|---|
| Material of Construction | Aluminum/sheet metal |
| ENVIRONMENTAL | |
| Relative Humidity | 0-95% non-condensing |
| SPECIAL FEATURES | |
| TVSS Grounding | Main grounding screw for connecting inverter to earth, vehicle, or boat grounding systems |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies