



2400-2483 MHz OPERATION FLAT PANEL DIRECTIONAL ANTENNA

The 2.4 GHz flat panel directional antennas by Laird offer high gain in a thin low profile package. The antennas are constructed of a gray color UV resistant ABS plastic radome with an aluminum backplate. The antenna can be used in horizontal or vertical polarization. The die cast aluminum or galvanized steel bracket affords +/- 45 deg up or down tilt adjustment and the stainless steel hardware assures a long service life. The PA24-13 and PA24-19 antenna can be surface mounted or pole mounted. The PA24-16 is pole mounted only. All antennas comes with an integral N female connector standard.


FEATURES

- High gain / low profile
- Pole mount or surface mount
- Rugged and weatherproof
- Vertical or horizontal polarization
- Type N female connector


MARKETS

- Wireless LAN applications
- Client antennas
- 802.11b/g applications
- OEM wireless data
- WiMAX


ANTENNA PATTERNS



PA24-13



PA24-16



PA24-19

Americas: +1.847 839.6925
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

SPECIFICATIONS

PARAMETER	PA24-13	PA24-16	PA24-19
Frequency range	2400 - 2483 MHz	2400 - 2483 MHz	2400 - 2483 MHz
Gain	13 dBi	16 dBi	19 dBi
3dB beamwidth (H & V)	35°	26°	17.5°
Front to back	20 dB	27 dB	30 dB
Cross polarization	-20 dB	-20 dB	-20 dB
VSWR	1.5:1	1.5:1	1.5:1
Impedance	50 ohm		50 ohm
Input power	100 watts		100 watts
Operating temperature	-40° to +70°C	-40° to +70°C	-40° to +70°C
Pole size	1 to 2 in (25 to 50 mm)	1 to 2 in (25 to 50 mm)	1 to 2 in (25 to 50 mm)
Weight	17.6 oz (0.5 kg)	31.5 oz (0.9 kg)	60 oz (1.7 kg)
Dimension (dia x depth)	7.5 x 7.5 x 0.8 in (190 x 190 x 20 mm)	11 x 11 x 0.8 in (279 x 279 x 20 mm)	15.3 x 14.6 x 0.8 in (389 x 368 x 20 mm)
Bracket tilt	45°	45°	45°

WIND LOADING (LBS.)

MODEL	SQ. IN	100 MPH	125 MPH	100 MPH WITH ½ IN RADIAL ICE
PA24-13	56	14 lbs	22 lbs	14 lbs
PA24-16	121	30 lbs	47 lbs	32 lbs
PA24-19	163	41 lbs	64 lbs	41 lbs

SYSTEM ORDERING

PA24-13 2.4 GHz 13 dBi flat panel directional antenna
 PA24-16 2.4 GHz 16 dBi flat panel directional antenna
 PA24-19 2.4 GHz 19 dBi flat panel directional antenna

NOTES

- All shipments F.O.B. Schaumburg, IL 60173

ANT-DS-PA24 1115

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trademarks or registered trademarks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.